

TDS X2O Masonry Cleaner

X₂O

PREMIUM CLEANER

PURJ

CLEAN
SEAL
RESTORE

MULTI-SURFACE
CITRUS CLEANER & DEGREASER

PURJ X2O Multi-Surface Citrus Cleaner

Directions for Application:

(1 Quart of concentrate makes 2 gallons of mixed cleaner)

Mixing: 1 Gallon

- 1-Remove 16oz plastic cup from top of box
- 2-Close top lid & lock tab. Push in top finger slot
- 3-Push In Red Circle and Remove
- 4-Pull TAB Forward
- 5-Pull out spout & lock into circle
- 6-Push TAB back in & secure into groove
- 7-Remove safety tab on spout
- 8-Fill a 1 gal pump sprayer or container approx half way with water
- 9-Fill included 1 16oz cup contents & pour into 1 gal water container
- 10-Top off rest of gallon with water up to 1 gal line, close lid & shake

Uses: Driveways, Patios, Sidewalks, Retaining Walls, Knee Walls, LedgeStone, Stone Veneering, Patio Furniture, Outdoor Kitchens, Decking

Cleaning: For dirt, grime & debris. **Spray entire surface area.**

Lightly scrub to foam up with deck brush. Let sit for 15 min.

If surface area dries, re-wet with water mist. Scrub & work into area with a bristle brush or clean with a power washer.

Rinse the surface thoroughly.

Spot Cleaning: Spray area & scrub to foam up. Let sit for 15 mins. Scrub with deck brush and rinse. For stubborn stains e.g. oil stains use **Undiluted**. Pour the concentrate on affected areas & let sit for 1 hour **minimum**. Scrub and rinse. Repeat applications may lighten stains, but not remove stains completely.

Power Washer Cleaning: Pour **Undiluted** product into pressure washer reservoir. Spray entire surface with low pressure on medium or maximum soap setting. Lightly scrub to foam up with deck brush. Let sit for 15 min. Use a surface cleaner or fan sprayer to clean. Rinse the surface thoroughly.

Notes: Always test an inconspicuous spot first. Visit our website at cleansealrestore.com for more product details & how to videos.

Maintenance: For all purpose cleaning. Works great for all sealed masonry surfaces. Spray area & scrub to foam up. Let sit for 15 mins. Scrub with deck brush or power washer fan sprayer and rinse.

Coverage: Approx. 150-200 sq ft per mixed gal for most surfaces. Depends on cleaning type, porosity, surface texture & temperature.

Clean Up: Rinse equipment with water.

Packaging Size: 1 Quart

WARNING: KEEP OUT OF REACH OF CHILDREN AND PETS

Skin Protection: Wear chemical resistant gloves & protective clothing

Eye Protection: Wear chemical safety goggles with a face shield

Respiratory Protection: An approved respirator with N95 (dust, fumes, mist) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure.

FIRST AID MEASURES

Inhalation: If inhalation of mists, vapors, or spray occurs and adverse effects result, remove to uncontaminated area.

Evaluate ABC's (is Airway constricted, is Breathing occurring, and is blood Circulating) and treat symptomatically. Get medical attention if needed.

Eye Contact: Immediately flush contaminated eyes with a directed stream of water for as long as possible.

Remove contact lenses, if present and easy to do.

Continue rinsing. Washing eyes within several seconds is essential to achieve maximum effectiveness. Get medical attention if needed.

Skin Contact: Immediately flush contaminated areas with water. Wash with large amounts of water. Get medical attention if needed. Thoroughly clean and dry contaminated clothing before reuse.

Ingestion: If swallowed, do not induce vomiting.

For definite or probable ingestion, do not administer oral fluids. If vomiting occurs spontaneously, keep airway clear. Monitor airway. Volume resuscitation (IV fluids) and circulatory support (CPR) may be required. Never give anything by mouth to an unconscious or convulsive person. **GET MEDICAL ATTENTION IMMEDIATELY.**

Handling: Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not ingest. Do not eat, drink or smoke in areas where this material is used. Wear personal protective equipment. When mixing, slowly add to water to minimize heat generation and spattering.

Storage: Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated from incompatible substances

SDS available upon request: info@cleansealrestore.com

Product Warranty: Clean Seal Restore, Inc. warrants X2O Cleaner to the original purchaser or end user, that when applied and maintained as directed, will perform as represented and claimed. This warranty is NOT transferable. In the event of failure, the only obligation of Clean Seal Restore, Inc. shall be to replace such products proven to be defective for reapplication to the area. Before application, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product. The product warranty does not extend to or cover misapplication or misuse of the product, including the use of abrasive or harsh cleaners or application tools, excessive soiling from lack of proper cleaning or neglect; wear and tear of the surface resulting from prior damage and exposure to weathering or abrasion. Clean Seal Restore, Inc. will not be liable or responsible for any damages to property or costs associated with the warranty, including any labor or equipment cost associated with re-application of the product by the original purchaser or end user as registered, for the intended application area.

Please use the product as instructed on the original label for complete details and safety measures.

