

# TDS Infuse Plus Masonry Sealer

## Infuse Plus

### MASONRY SEALER

# PURJ

CLEAN  
SEAL  
RESTORE

MULTI-SURFACE  
OIL & WATER REPELLENT

#### **PURJ Infuse Plus Multi-Surface Masonry Sealer**

#### **Directions for Application (Interior and Exterior)**

(1 Quart of concentrate makes 3 gallons of mixed sealer)

#### **Mixing:** 1 Gallon

- 1-Remove 10oz plastic cup from top of box
- 2-Close top lid & lock tab. Push in top finger slot
- 3-Push In Red Circle and Remove
- 4-Pull TAB Forward
- 5-Pull out spout & lock into circle
- 6-Push TAB back in & secure into groove
- 7-Remove safety tab on spout
- 8-Fill a 1 gal pump sprayer or container approx half way with water
- 9-Fill included 1 10oz cup contents & pour into 1 gal water container
- 10-Top off rest of gallon with water up to 1 gal line, close lid & shake

**Uses:** Driveways, Sidewalks, Patios, Steps, Retaining Walls, Knee Walls, Ledgestone, Stone Veneering, Fire Pit, Outdoor Kitchens, etc..

**Surface Prep:** Before sealing, surfaces should be clean & free of efflorescence, debris, oil, grease, rust stains, leaf & berry stains, algae, waxes, sealers, etc. Cleaned surfaces will allow the sealer to absorb and perform effectively.

For recommended cleaners, product details & how to videos visit:

[cleansealrestore.com](http://cleansealrestore.com)

**Horizontal Surfaces:** e.g. driveways & patios. Apply 1-2 even liberal coats of **Infuse Plus Sealer** using a 1/2" - 3/4" nap roller, paint pad, or brush.

**Do Not Spray.** Rolling is recommended to assure optimal even coverage.

**Vertical Surfaces:** e.g. stone veneering & knee walls.

Apply ONE even liberal coat of **Infuse Plus Sealer** with a low-pressure sprayer, roller, paint pad or brush.

Start from the bottom & apply upward.

**Notes:** A second coat may be needed for very porous surfaces. If so, sealer should be applied within 15 minutes max from the 1st coat.

Do not apply sealer if rain is expected in a few hours.

Test in an inconspicuous area before starting the general application to ensure desired results.

**Infuse Plus** penetrates below the surface so it will not prevent surface etching, scuff marks or any surface wear.

During sealing application, if the surface area fully dries & the stop line is not visible, overlap a few inches as the sealed area should repel and the unsealed area will darken. It is recommended to seal cement & natural stone pavers prior to applying polymeric sand and cement joints.

This will help prevent poly haze and grout staining (shadowing), especially on bluestone pavers.

Re-apply sealer to cement joints after grouting for added protection.

Be sure to thoroughly clean **prior** to re-applying more sealer.

Wait 12-24 hours for grout to cure before applying sealer.

If spills occur, they should be cleaned as soon as possible as to avoid potential penetration.

Oil Repellent Sealers **help prevent** oil &

water penetration and may not block oils 100%, depending on the volume, type of oil & how long it dwells.

If oil is left too long & staining is visible, clean with

**X20 CITRUS CLEANER** full strength or undiluted. Dish soap e.g.

Dawn undiluted is an alternative. Repeat process if necessary.

\*Keep work area well-ventilated while applying sealer

\*Do not inhale spray, wear suitable organic respirator

\*Sealer can be applied to dry or damp surfaces

\*Surface temperature should be between 50-90°F (10-32°C)

\*Use of the treated surface may resume in 2-4 hours

\*A full cure is achieved in 24-72 hours

**Clean Up:** Clean rollers, brushes and equipment with soap and water.

**Maintenance:** Spills should be cleaned as soon as possible as to avoid potential penetration. All sealed areas can be cleaned with **X20 CITRUS CLEANER** Medium Strength or a mild neutral cleaner.

**Coverage:** Approx. 100-120 sq ft per mixed gal for most masonry surfaces.

Depends on porosity, surface texture, temperature & method of application.

**Packaging size:** 1 Quart of concentrate makes 3 gallons of mixed sealer.

**Expected Wear:** Approximately 2-4 years for interior and exterior depending on use.

**WARNING: KEEP OUT OF REACH OF CHILDREN AND PETS**

**Skin Protection:** Protective gloves & clothing

**Eye Protection:** Use chemical splash goggles and face shield

**First Aid Measures:**

**Inhalation:** If aerosol or mists are inhaled, take affected persons out into the fresh air.

In case of persistent discomfort or other symptoms, consult a physician immediately.

**Skin Contact:** Immediately wash skin with soap and plenty of water.

Remove contaminated clothing.

Obtain medical attention immediately if symptoms occur. Wash clothing before reuse.

**Eye contact:** Rinse thoroughly with plenty of water keeping eyelid open.

In case of persistent discomfort: Consult an ophthalmologist.

**Ingestion:** Have the mouth rinsed with water. After absorbing large amounts of substance / In case of discomfort: Supply with medical care.

**Handling:** Do not breathe in vapours or aerosols. This may cause respiratory complications.

Handle in accordance with good industrial hygiene and safety practice.

Wear suitable protective equipment.

Avoid contact with eyes, skin, and clothing. If there is the possibility of skin/eye contact, the indicated hand/eye/body protection should be used.

Use with adequate ventilation. Wash thoroughly after handling.

**Storage:** Keep tightly sealed in original packaging. Protect from frost.

**Product Warranty:** Clean Seal Restore, Inc. warrants Infuse Plus Sealer to the original purchaser or end user, that when applied and maintained as directed, will perform as represented and claimed.

This warranty is NOT transferable. In the event of failure, the only obligation of Clean Seal Restore, Inc. shall be to replace such products proven to be defective for reapplication to the area.

Before application, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.

Neither seller nor manufacturer shall be liable for any injury or inability to use this product. The product warranty does not extend to or cover misapplication or

misuse of the product, including the use of abrasive or harsh cleaners or application tools, excessive soiling from lack of proper cleaning or neglect; wear

and tear of the surface resulting from prior damage and exposure to weathering or abrasion. Clean Seal Restore, Inc. will not be liable or responsible for any damages

to property or costs associated with the warranty, including any labor or equipment cost associated with re-application of the product by the original

purchaser or end user as registered, for the intended application area.

**Please use the product as instructed on the original label for complete details and safety measures.**

**FOR EMERGENCY MEDICAL**

**ASSISTANCE CALL YOUR LOCAL**

**POISON CONTROL CENTER**

Contains: Fluorocarbon